

Linea Jungle



For suspended ceiling:

- Panel **TO BE INSTALLED** on T24 frame
- Panel **TO BE SCREWED** onto metal or wooden frame

INSTALLATION:


In accordance with NF EN 13964
In accordance with DTU 58-1

For wall cladding:

- Panel **TO BE SCREWED** onto metal or wooden frame

INSTALLATION:

In accordance with NF EN 14915
In accordance with DTU 36-2



TECHNICAL SPECIFICATIONS

Panel dimensions	2,495 x 600 mm (screw-on only) 1,880 x 600 mm 1265 x 600 mm
Slat cross-section	40 mm (front) x 41 mm (height)
Slat spacing	35 mm
Centre distance of slats:	75 mm
Black rear counter-slats	34 x 45 mm
Total thickness	76 mm
Timber species	Pine, oak
Area density, pine	12.5 kg/m ²
Area density, oak	14.4 kg/m ²
Openness percentage	47%

Back: rigid acoustic rockwool tiles (2.4 kg/m²), covered with black fleece finish (size: 600 x 600 mm; thickness: 20 or 22 mm).

Not supplied by Laudescher.

REACTION TO FIRE (IN ACCORDANCE WITH EN 13501-1)

Fire-retardant, Euroclass standard B-s1, d0 or B-s2, d0 depending on the type of wood and finish.


ACOUSTIC PERFORMANCE

Various items of sound absorption data (α_p , α_w , absorption class) have been calculated in accordance with standard ISO 11654 (Linea + acoustic complement).

LINEA JUNGLE CEILING

+ 20 mm rockwool on E250mm plenum

ACOUSTIC ABSORPTION RATING




WEIGHTED INDEX:
 $\alpha_w = 0.70$

ABSORPTION CLASS:
Class C

LINEA JUNGLE WALL

+ 20 mm rockwool on E50mm plenum

ACOUSTIC ABSORPTION RATING



WEIGHTED INDEX:
 $\alpha_w = 0.85$

ABSORPTION CLASS:
Class B



TO BE INSTALLED



TO BE SCREWED ON

